



Specifications

7000C

Log Max 7000C combines high traction with fast feed speed and is one of our most popular heads. The traction and speed of the head are automatically adjusted depending on the size of the trees, which brings smooth log feeding and a good driving experience.

Dimension and Weight

Weight	1646 kg
Height	1742 mm
Width Roller Arms Open	1937 mm
Width Roller Arms Closed	1315 mm

Felling and Cutting

Optional Saw Models	Saw 98XL, SuperCut - 19cc, SuperCut - 30cc
Optional Saw Tensioner	Automatic, manual
Top Saw Models	
Top Saw Tensioner	
Saw Oil Capacity	36 liters
Max Saw Bar Length	900 mm
Max Cut Capacity	750 mm

Delimbing

Number of Delimbing Knives	4
Max Delimbing Knife Opening	757 mm
Max Delimbing Full Coverage	530 mm

Feeding

Feed Roller Models	V-STEEL SOFT GRIP, V-STEEL HARD GRIP, Eucalyptus
Feed Roller Motors	Variabel 830-1320 cc, 1147 cc

Max Feed Force	41.7 kN
Max Feed Speed	5.3 m/s
Max Feed Roller Opening	713 mm
Min Feed Roller Opening	13 mm

Hydraulics

Max Pressure	300 bar
Min Pressure	0 bar
Max Flow	300 l/min
Min Flow	200 l/min

Rotators

Rotators	Indexator AV17S, Indexator H182
----------	---------------------------------

Base machine

Excavator Max Weight	35 ton
Excavator Min Weight	21 ton
Wheeled Harvester Max Weight	25 ton
Wheeled Harvester Min Weight	18 ton
Tractor	ton
Crane Requirements Max	300 kNm
Crane Requirements Min	200 kNm

Control Systems

Control Systems	Log Mate 510
-----------------	--------------

* Standard and extra equipment are market-dependent and vary between countries. The specification describes possible equipment, not that which is standard or optional. Stated weights are based on standard equipment. Specifications and designs are subject to change without notice.